

UNITED STATES PATENT APPLICATION FOR:

ELECTROLESS PLATING SYSTEM

INVENTORS:

**JOSEPH J. STEVENS
DMITRY LUBOMIRSKY
IAN PANCHAM
DONALD J. K. OLGADO
HOWARD E. GRUNES
YEUK-FAI EDWIN MOK
GIRISH DIXIT**

ATTORNEY DOCKET NUMBER: AMAT/6120/CPI/ECP/PJS

CERTIFICATION OF MAILING UNDER 37 C.F.R. 1.10

I hereby certify that this New Application and the documents referred to as enclosed therein are being deposited with the United States Postal Service on 12/26/01, in an envelope marked as "Express Mail United States Postal Service", Mailing Label No. EL913564858US, addressed to: Assistant Commissioner for Patents, Box PATENT APPLICATION, Washington, D.C. 20231.



Signature

N. ALEXANDER NOURI

Name

12/26/01

Date of signature

ELECTROLESS PLATING SYSTEM

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The present invention generally relates to a an electroless plating system.

Description of the Related Art

[0002] Sub-quarter micron multilevel metallization is a key technology for the next generation of very large scale integration (VLSI) and ultra large scale integration (ULSI). The multilevel interconnects that lie at the heart of these integration technologies possess high aspect ratio features, including contacts, vias, lines, plugs, and other features. Therefore, reliable formation of these features is critical to the success of VLSI and ULSI, as well as to the continued effort to increase integrated circuit density, quality, and reliability on individual substrates. As such, there is a substantial amount of ongoing effort being directed to improving the formation of void-free sub-quarter micron features having high aspect ratios, *i.e.*, features having a height to width ratio of about 4:1 or greater.

[0003] Elemental aluminum (Al) and aluminum alloys have conventionally been used as conductive materials to form lines, plugs, and other features in integrated circuit semiconductor processing techniques, as a result of aluminum's low resistivity, superior adhesion to silicon dioxide (SiO₂) substrates, ease of patterning, and relatively high purity available at moderate costs. Aluminum, however, suffers from a relatively high resistivity, as well as poor electromigration characteristics. Therefore, and as the width of electrical interconnections becomes narrower, *i.e.*, into the sub-quarter micron range, the resistance and electromigration characteristics of aluminum has an increasingly negative affect upon the resistance-capacitance (RC) time delay characteristics of the integrated circuits formed using aluminum interconnect features. As a result of the disadvantages of aluminum, copper and copper alloys have recently become choice metals for filling sub-quarter micron high aspect ratio interconnect features in integrated circuits, as copper and

copper alloys have a lower resistivity than aluminum, and therefore, generate RC circuits having better time delay characteristics.

[0004] However, a problem with using copper in integrated circuit fabrication is that copper is not easily deposited into high aspect ratio features with conventional semiconductor processing techniques. For example, physical vapor deposition (PVD) techniques may be used to deposit copper, however, PVD copper deposition is known to encounter difficulty in obtaining adequate bottom fill in high aspect ratio features. Additionally, chemical vapor deposition (CVD) may be used to deposit copper, however, CVD suffers from low deposition rates, and therefore low throughput, in addition to using precursors that are generally unstable.

[0005] Therefore, there exists a need for an apparatus for reliably depositing copper into high aspect ratio features of integrated circuits.

SUMMARY OF THE INVENTION

[0006] Embodiments of the invention generally provide a method and apparatus for plating substrates. An exemplary plating apparatus of the invention includes a central substrate transfer enclosure having at least one substrate transfer robot positioned therein. A substrate activation chamber in communication with the central substrate transfer enclosure is provided and is accessible to the at least one substrate transfer robot. A substrate plating chamber in communication with the central substrate transfer enclosure is provided and is accessible to the at least one substrate transfer robot. A substrate spin rinse dry chamber in communication with the central substrate transfer enclosure is provided and is accessible to the at least one substrate transfer robot, and an annealing chamber in communication with the central substrate transfer enclosure is provided and is accessible to the at least one substrate transfer robot. At least one substrate pod loader in communication with the substrate transfer chamber and accessible to the at least one substrate transfer robot is also provided.

[0007] Embodiments of the invention further provide a semiconductor plating system that includes a central transfer enclosure, a first substrate transfer robot

PATENT

Attorney Docket No.: AMAT/6120/CPI/ECP/PJS

Express Mail No.: EL913564858US

positioned in a first region of the substrate transfer enclosure, and a second substrate transfer robot positioned in a second region of the substrate transfer enclosure. A first substrate pod loader in communication with the first region of the substrate transfer enclosure is provided, and a second substrate pod loader in communication with the second region of the substrate transfer enclosure is also provided. An activation enclosure in communication with the first region of the substrate transfer enclosure is provided and a substrate plating enclosure in communication with the first region of the substrate transfer enclosure is provided. A substrate spin, rinse dry enclosure in communication with the second region of the substrate transfer enclosure is provided and a substrate annealing enclosure in communication with the second region of the substrate transfer enclosure is provided. A substrate handoff is provided and is positioned in the substrate transfer enclosure and in communication with the first region and the second region.

[0008] Embodiments of the invention further provide a method for plating a metal on a substrate, wherein the method includes the steps of retrieving a substrate from a first pod loader position with a first substrate transfer robot positioned in a substrate transfer enclosure and transferring the substrate to an activation chamber in communication with the substrate transfer enclosure for an activation process with the first substrate transfer robot. The method further includes removing the substrate from the activation chamber with the first substrate transfer robot and transferring the substrate to a plating enclosure in communication with the substrate transfer enclosure for a plating process, and then removing the substrate from the plating enclosure with the first substrate transfer robot and positioning the substrate on a handoff position in the substrate transfer enclosure. The method further includes retrieving the substrate from the handoff position with a second substrate transfer robot positioned in the substrate transfer enclosure and transferring the substrate to a spin rinse dry enclosure in communication with the substrate transfer enclosure for a rinse and dry process, and removing the substrate from the spin rinse dry enclosure with the second robot and transferring the substrate to an annealing chamber in communication with the substrate transfer enclosure for an annealing process. Once the annealing process is complete, the method includes

the step of transferring the substrate to a second pod loader in communication with the substrate transfer enclosure with the second substrate transfer robot.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] So that the manner in which the above recited features, advantages and objects of the present invention are attained and can be understood in detail, a more particular description of the invention, briefly summarized above, may be had by reference to the embodiments thereof which are illustrated in the appended drawings. It is to be noted, however, that the appended drawings illustrate only typical embodiments of this invention and are therefore not to be considered limiting of its scope, for the invention may admit to other equally effective embodiments.

[0010] Figure 1 illustrates an exemplary plating system configuration of the invention.

[0011] Figure 2 illustrates an exemplary activation chamber of the invention.

[0012] Figure 3A illustrates an exemplary face up-type electroless plating chamber of the invention.

[0013] Figure 3B illustrates a sectional view of a central portion of the substrate support member shown in the embodiment illustrated in Figure 3A

[0014] Figure 4A illustrates an exemplary plating chamber of the invention.

[0015] Figure 4B illustrates a detailed sectional view of an outer portion of the substrate support member of the exemplary plating chamber illustrated in Figure 4A.

[0016] Figure 4C illustrates an exemplary sectional view of a substrate support member and an evaporation shield of the exemplary plating chamber illustrated in Figure 4A during a plating process.

[0017] Figure 4D illustrates an exemplary sectional view of a substrate support member, evaporation shield, and outer seal of an exemplary plating chamber of the invention.

[0018] Figure 5A illustrates an exemplary face down plating system that may be implemented into the plating system of the invention.

[0019] Figure 5B illustrates a sectional view of an exemplary substrate support member and plating shield of the plating chamber embodiment illustrated in Figure 5A.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0020] The present invention generally provides an electroless plating system configured to plate copper onto semiconductor substrates having high aspect ratio features formed thereon. Figure 1 illustrates an exemplary plating system 100 of the invention, wherein the plating system 100 includes a central substrate transfer chamber 101 having at least one substrate transfer robot 102 positioned therein. A substrate handoff position or substrate orienter 103 may be interstitially positioned between robots 102. Each of robots 102 may be configured to access at least one substrate pod loader, at least two substrate processing chambers, and the substrate handoff position. For example, a first substrate transfer robot 102 may be positioned in a first region of enclosure/chamber 101, *i.e.*, the right side of enclosure 101, while a second substrate transfer robot 102 may be positioned in a second region of enclosure 101, *i.e.*, the left side of enclosure 101, as illustrated in Figure 1. Substrate transfer chamber 101 may be in communication with a vacuum system (not shown), and therefore, may be maintained at a reduced pressure in order to reduce substrate contamination. Alternatively, chamber 101 may comprise an enclosure that is maintained at atmospheric pressure. However, if the enclosure configuration is utilized, then an air filtration system may be implemented in order to reduce contamination elements in the substrate enclosure region. Chamber 101 may also include a plurality of openings 110, *i.e.*, slit valves, positioned about the perimeter thereof for communicating substrates from chamber 101 via robots 102 to various processing chambers or storage elements that may be attached to chamber 101 via openings/valves 110.

[0021] One or more substrate pod loaders 104, 105 may be in communication with the substrate transfer chamber 101. Pod loaders 104, 105 may generally be configured to store substrates therein in a manner that allows robots 102 to access the substrates, *i.e.*, by receiving substrate cassettes therein. As such, for example, pod loader 104 may be filled with new substrates that are designated for processing, while pod loader 105 may be an empty pod loader configured to receive processed substrates therein. Processing chamber 106 may be configured as an electroless activation chamber. In this configuration, chamber 106 may receive a new substrate pulled from pod loader 104 by robot 102 therein for activation processing prior to electroless plating. Processing chamber 107 may be configured as an electroless deposition chamber, and therefore, chamber 107 may receive a substrate from activation chamber 106 via robot 102. Processing chamber 108 may be configured as a spin rinse dry (SRD) chamber, and therefore, SRD chamber 108 may receive a substrate from plating chamber 107 via robot 102 for rinsing and drying of the substrate subsequent to the plating process. Processing chamber 109 may be configured as a substrate annealing chamber, and therefore, annealing chamber 109 may receive a substrate from SRD chamber 108 for annealing subsequent to the spin rinse dry process.

[0022] System 100 is generally configured to process/plate substrates in a unitary apparatus/system, *i.e.*, substrates to be plated are input into system 100 and plated substrates are output without transferring the substrates to another processing chamber/system. Therefore, system 100 offers an integrated processing system capable of activating a substrate for plating, rinsing a substrate before plating, plating a substrate, spin rinse drying a substrate, and annealing a substrate, all in a unitary processing system. The unitary/integrated processing system 100 allows for reduced contamination, reduced defect ratios, and increased throughput over conventional plating systems. Furthermore, as a result of the integrated/unitary configuration, system 100 uses a substantially smaller footprint than conventional plating systems. This is also a significant advantage, as a reduced footprint yields a reduction in the clean room space required to support system 100, which reduces operating costs.

PATENT

Attorney Docket No.: AMAT/6120/CPI/ECP/PJS

Express Mail No.: EL913564858US

[0023] Figure 2 illustrates an exemplary clean-in-clean-out activation chamber/enclosure 106 of the invention. Activation chamber/enclosure 106 includes a processing compartment 202 having a top portion 204, sidewalls 206, and a tapered or sloping bottom portion 207. A substrate support 212 is disposed in a generally central location in chamber 106. The substrate support 212 includes a substrate receiving surface 214 configured to receive and secure a substrate 210 thereon in a "face-up" position, *i.e.*, the production surface of the substrate is facing away from the substrate support member. The receiving surface 214 may also include an annular drain channel (not shown) formed proximate the perimeter of the substrate receiving surface 214. The drain channel may operate to direct fluid running off of the edge of the substrate away from the substrate support member 212, which minimizes the chemical reaction therewith and the potential for chamber contamination. Substrate support 212 may include a vacuum port 224 positioned on the receiving surface 214 and in communication with a vacuum source (not shown). Vacuum port 224 may therefore be used to supply a negative pressure to the backside of substrate 210 in order to vacuum chuck the substrate 210 to the substrate support 212. Vacuum grooves or apertures 226 may be formed into receiving surface 214 and may be in communication with vacuum port 224 for the purpose of distributing the vacuum chucking force.

[0024] Substrate support 212 may be manufactured from a ceramic material, such as alumina Al_2O_3 , a TEFLONTM coated metal (such as aluminum or stainless steel), silicon carbide (SiC), or other suitable materials known in the semiconductor processing technology. TEFLONTM, as used herein, is a generic name for fluorinated polymers such as Tefzel (ETFE), Halar (ECTFE), PFA, PTFE, FEP, PVDF, etc. Chamber 106 may further include an opening, such as a slit valve 208, for example, formed through sidewall 106, which provides access for substrate transfer robot 102 to deliver and retrieve substrates to and from chamber 106. In an alternative configuration, substrate support 212 may raise substrate 210 through the top 204 of the processing compartment 202 to provide access to and from the chamber 106 via a lift actuator assembly 216 disposed below substrate support member 212. Lift actuator assembly 216 may include lift pins 218 that are

configured to selectively raise or lower substrate 210 via vertical actuation thereof through apertures 220 formed into substrate support member 212. Therefore, lift pins 218 may operate to raise and lower substrate 210 off of substrate receiving surface 214 for removal from chamber 106 by a substrate transfer robot 102 configured to access chamber 106 from the top portion 204 thereof.

[0025] A motor 222 may be coupled to substrate support 212 in order to impart rotational motion thereto, which operates to spin the substrate 210 positioned on substrate support member 212. In one embodiment, the lift pins 218 may be disposed in a lower position below the substrate support 212 to allow the substrate support 112 to rotate independently of the lift pins 218. In another embodiment, the lift pins 218 may concomitantly rotate with substrate support 212. Substrate support 212 may be heated through resistive heater elements (not shown) formed therein, which may operate to selectively heat substrate 210 to a desired processing or activation temperature. The substrate receiving surface 214 of the substrate support 212 may be sized to substantially receive the backside of the substrate 210 in order to provide uniform heating of the substrate 210, which is known to reduce first wafer effects and initiation time for activation chamber 106, thus increasing the efficiency and throughput of the activation process.

[0026] A fluid distribution member or device, such as a nozzle 223, may be disposed in chamber 106 and configured to deliver a fluid, such as a chemical processing solution, an activation solution, deionized water, an acid solution, or other chemical solution that may be used in an electroless plating activation process, to the surface of the substrate 210. Nozzle 223 is generally disposed on a pivotally mounted dispense arm 222 that is rotatably moveable about support member 221. Therefore, nozzle 223 is adapted to pivot about the axis of support member 221, which allows nozzle 223 to be radially positioned over the substrate 210, pivoting in an arc corresponding to the radius of the dispense arm 222. As such, nozzle 223 may be pivoted from a position immediately above the center of substrate 210 through an arc over the surface of the substrate 210 to the perimeter of the substrate 210. Further, although dispense arm 222 is illustrated in Figure 2 as

being mounted inside chamber 106, embodiments of the invention contemplate that the arm and nozzle assembly may be mounted outside chamber/enclosure 106 and dispense an activation solution onto substrate 210 through an open top-type configuration with equal effectiveness. Additionally, a nozzle 223 may be configured to distribute the activation fluid in an outward direction from the center of a substrate when nozzle 223 is positioned above the center of the substrate. The configuration of nozzle 223 allows the activation chamber's 106 effluent stream to be minimized, which in return minimizes COO issues in chamber 106.

[0027] At least one fluid source 228, which may contain activation solutions and rinse solutions, may be coupled to nozzle 223 via a conduit running through an interior portion of support member 221, arm member 222, and nozzle 223. Flow control valves 229 may be coupled between the fluid sources 228 and the interior portion of support member 221 in order to selectively vary fluid mixtures, concentrations, or other fluid properties varied in activation processes. The fluid sources 228 may be controlled by an automated system, such as a microprocessor-based control system (not shown), in order to accurately manage the activation solution mixture and flow to nozzle 223. As a result of the multiple fluid sources 228, the substrate 210 may be both rinsed and have an activation solution applied thereto in chamber 106.

[0028] The rotation of substrate support member 212 may be regulated or controlled through selective application of electrical power to motor 222. The regulation or control of motor 216 may be accomplished by a microprocessor based control system (not shown) configured to selectively apply electrical power to motor 216 in accordance with a processing recipe, a predetermined rotation sequence, user specifications, or other parameters that may be used to control rotation of a substrate in a semiconductor processing chamber/enclosure. Therefore, the substrate support member 212 may be rotated at relatively slow speeds, such as between about 5 RPM and about 500 RPM, during the a time period when a rinsing solution or a activation solution is being dispensed on the substrate surface. The low rotation speed operates to facilitate effective rinsing and even spreading of the

PATENT

Attorney Docket No.: AMAT/6120/CPI/ECP/PJS

Express Mail No.: EL913564858US

activation solution across the surface of the substrate, in a similar manner to a spin on process. Following a rinsing or activation solution dispensing process, the substrate support member 212 may be rotated at higher rotation rates in order to remove any excess activation or rinsing solution from the substrate surface, in similar fashion to a spin dry process. These higher rotation rates may be as high as 10,000 RPM, if necessary. Additionally, substrate support 212 may be adapted to reverse spin direction or spin in alternating directions in order to further facilitate even spreading of the activation fluid across the surface of substrate 210, if desired. Chamber 106 further includes a drain 227 positioned on the lower or bottom portion of chamber 106. Drain 227 operates to collect the fluid (activation solution or rinsing solution) that runs off of the tapered/sloped portion of bottom 207. Although conventional activation processing schemes only use the activation solution once, *i.e.*, there is no reclamation or recycling of the used activation fluid, drain 227 may be in communication with an activation fluid reclamation or recycling apparatus configured to reclaim activation fluids used in chamber 106 for use in additional activation processes.

[0029] Figure 3A illustrates an embodiment of an exemplary face up-type plating chamber/enclosure 107 of the invention. Exemplary plating chamber 300 is similar in structure to activation chamber 106 shown in Figure 2, *i.e.*, plating chamber 300 includes a bottom portion, sidewalls, a top portion, a slit valve, and a centrally positioned substrate support member 301 positioned therein. Substrate support member 301 includes an upper substrate receiving surface 303 configured to support a substrate 302 thereon for processing. Substrate receiving surface 303 includes a vacuum aperture 304 centrally positioned on the substrate receiving surface 303. Vacuum aperture 304 may be in communication with a vacuum source (not shown) and include a hoop vacuum seal 305 positioned about the perimeter of vacuum aperture 304, as shown in Figure 3B. Hoop seal 305 is generally configured to sealably engage the bottom or backside of substrate 302 in order to vacuum chuck the substrate 302 to the substrate receiving surface 303 for processing. Substrate support member 301 may also include a vacuum seal 306 positioned radially outward from hoop seal 305. Vacuum seal 306 cooperatively

operates with hoop seal 305 to form a region of negative pressure behind the substrate 302 in the area of the between hoop seal 304 and vacuum seal 306. This area of negative pressure operates to vacuum chuck substrate 302 to substrate receiving surface 303.

[0030] Substrate receiving surface 303 additionally includes a liquid seal 307 positioned radially outward of vacuum seal 306 proximate the perimeter of receiving surface 303 of substrate support member 301. Liquid seal 307 generally operates to shed fluids dispensed on substrate 302 away from substrate support member 301, such that chemical reactions between the dispensed fluid and the substrate support member may be minimized, thus reducing chamber/enclosure contamination issues. Substrate support member 301 may additionally include a heater 316 disposed in an interior portion or on the substrate receiving surface of substrate support member 301. Heater 316, for example, may be a resistive heating element formed into an interior portion of substrate support member 301, which may be provided electrical power of via electrical contacts 308 extending from the bottom portion of substrate support member 301. Alternatively, substrate support member 301 may have fluid passages (not shown) formed therein such that a heated fluid may be flowed through the fluid passages in order to provide heat to substrate support member 301. Additionally, if desired for a specific plating operation, the fluid passages may be used to cool the substrate support member 301 by flowing a cooled fluid therethrough. The lower portion of substrate support member 301 includes a lift assembly 310 configured to actuate lift pins 309 for the purpose of elevating substrate 302 above the substrate receiving surface 303. Additionally, a motor of 311 is in communication with substrate support member 301 for the purpose of imparting rotational motion thereto.

[0031] Plating chamber 300 additionally includes a fluid dispensing device 312 positioned proximate the perimeter of substrate support member 301. Fluid dispensing device 312 generally includes a base member 313 that connects to an arm portion 314 that extends over the surface of the substrate 302. The terminating end of arm portion 314 includes a fluid dispensing nozzle 315 configured to

dispense plating fluids on the surface of substrate 302. Fluid dispensing nozzle 315 is in communication with a hollow interior portion of arm 314 and base member 313. The hollow interior portion of the arm and base member is in communication with a plating fluid supplying system 317. Fluid supply system 317, which is similar to the fluid supply system of the activation chamber 106 illustrated in Figure 2, generally includes a plurality of fluid sources 319 and fluid control valves 318. As such, the fluid supply system 317 may provide a plating solution to dispensing nozzle 315 via the hollow interior portions of arm 314 and base member 313, wherein the plating solution may be a combination of the contents of the several fluid sources 319.

[0032] Figure 4A illustrates a sectional view of an alternative embodiment of an electroless plating chamber of the invention. Plating chamber 400 again includes a chamber/enclosure having sidewalls, a bottom portion, and a top portion, in similar fashion the chambers illustrated in Figures 2 and 3. Chamber 400 also includes a rotatably mounted substrate support member 401 and a fluid dispense arm assembly 402. Therefore, chamber 400 again supports a substrate in a face up configuration for a plating process. However, chamber 400 additionally includes a plating evaporation shield 403 positioned immediately above the substrate support member 401. Plating evaporation shield may be mounted to a lid portion of the chamber 400 (not shown) or to an actuator assembly (not shown) that is configured to move evaporation shield between a processing position and a substrate loading position. Plating evaporation shield 403, which may be rotatably mounted, generally includes a hollow upper portion 409 attached to a disk shaped lower portion 410. Hollow upper portion 409 is configured to transmit a plating fluid received from a fluid dispense arm assembly 402 therethrough to the surface of a substrate positioned on substrate support member 401, and therefore, the hollow upper portion may operate as a plating fluid dispensing channel for communicating a plating fluid from a fluid source to the substrate surface. The disk shaped lower portion 410 generally includes a bore formed therein along the axis of the disk shaped lower member 410, wherein the bore is in fluid communication with the hollow upper portion 409. The lower surface of disk shaped lower member 410 is configured to be substantially planar and to be positioned in parallel orientation to

the upper surface of a substrate positioned on the substrate support member 401. Therefore, fluid dispensed by the fluid dispense arm assembly 402 is received by the hollow interior portion 409 and transmitted therethrough to the volume 408 defined by the upper surface of the substrate being processed and the lower surface of the disk shaped lower member 410, as shown in Figure 4C. As the fluid fills the volume 408, a meniscus 407 forms proximate the perimeter of the substrate being processed and the disk shaped lower member 410. Therefore, evaporation shield 403 may be rotated relative to substrate support member 401, such that the plating fluid contained in region 408 is caused to circulate via a turbulence effect. However, although the plating fluid in region 408 is circulating, meniscus 407 maintains the fluid in region 408, so that no additional fluid needs to be added to region 408 during the plating process. Additionally, evaporation shield 403 may be configured to counter rotate and or agitate with respect to substrate support member 401, which may operate to further the turbulent effect of the plating fluid contained in region 408.

[0033] As noted above, plating evaporation shield the 403 may be configured to be moved between a processing position, *i.e.*, a position where the lower surface of the disk shaped member 410 is proximate the substrate support member 401, and a loading positioned, *i.e.*, a position where a substrate transfer robot may gain access to chamber 400 for the purpose of inserting or removing substrates there from. In the processing position, plating evaporation shield may be positioned such that the distance from the upper surface of the substrate being processed to the lower surface of the disk shaped member 410 is between about .5 mm and about 5 mm, for example. However, it is contemplated that the spacing between the substrate and the evaporation shield 403 may be increased up to about 10 mm, for example. Regardless, the spacing between evaporation shield the 403 and substrate support member 401 is configured such that the meniscus 407 may be maintained when a plating fluid is introduced into region 408 and the respective members are rotated. Additionally, substrate support member 401 may include an annular gas channel 405 positioned proximate the perimeter of substrate support member 401, as shown in Figure 4B. Gas channel 405 may be in communication with a gas source (not

shown), and therefore, may be used to generate a gas shield or seal proximate the edge of the substrate being processed on the backside thereof. Thus, the plating fluid dispensed on the front side of the substrate being processed may be prevented from the traveling to the backside of the substrate and causing plating thereon by an outward gas flow from gas channel 405. Further, substrate support member 401 may include an annular fluid drain channel 406 formed into the upper surface of the substrate support member 401 radially outward of the gas channel 405 proximate the perimeter of substrate support member 401. The fluid drain channel 406 may be positioned immediately below the edge of the substrate being processed, and therefore, fluid drain channel 406 may receive any fluid runoff from the edge of the substrate. Fluid drain channel 406 may then communicate the fluid received therein through the substrate support member 401 to the lower portion of chamber 401 to be drained therefrom.

[0034] In an alternative embodiment of the plating chamber 400 shown in Figure 4A, the evaporation shield 403 may be modified to include an outer fluid seal 411, as shown in figure 4D. The outer fluid seal 411 may operate to maintain the fluid dispensed into the area between the evaporation shield 410 and the substrate. Seal 411 may be attached to evaporation shield 403, such that seal 411 is also movable between a processing position and a substrate loading position. Seal 411 may be useful in a configuration where the rotation rate of substrate support member 401 relative to evaporation shield 403 is high enough to overcome the meniscal force that holds the plating fluid in region 408. In this configuration, and seal 411 may be configured to abut against the edge of the substrate being processed in the exclusion zone region, such that the fluid in region 408 cannot travel into the fluid drain positioned proximate the edge of the substrate. Alternatively, seal 411 may be positioned proximate the edge of the substrate and not physically engage the substrate surface. Additionally, an outer seal 411 may be used to prevent plating fluid in from running in over the edge of substrate support member 401, *i.e.*, outer seal 411 may be used to direct any overflow fluid into the annular fluid drain 406 positioned radially inward from outer seal 411.

[0035] Figure 5A illustrates an alternative embodiment of plating chamber 107. The alternative plating chamber 500 generally includes a head assembly 501 configured to support a substrate from above, while suspending the substrate in a plating chamber 502 for processing. Therefore, in this configuration, the substrate is generally supported in a face down configuration, i.e., the production surface faces away from the support member in a downward direction, such that the plating solution may be delivered to the substrate in plating chamber 502 from below the substrate. Substrates may be placed into chamber 502 and removed from chamber 502 via vertical movement of head assembly 501. The lower portion of head assembly 501 generally includes a rotatably mounted substrate support member 503 configured to support a substrate on a lower surface 504 thereof. The lower surface 504 may include a vacuum chuck assembly, a mechanical chuck assembly, or other device/assembly configured to secure a substrate thereto. Plating chamber 502 includes a substantially planar bowl portion 507 centrally positioned in plating chamber 502. Bowl portion 507 includes a centrally disposed fluid injection/reclaim port 506. Port 506 may be in communication with a plating fluid supply (not shown) and may be configured to dispense a plating fluid from the fluid supply to bowl portion 507. Port 506 may also be used as a reclamation port, as port 506 may selectively be in communication with a plating fluid reclamation device (not shown).

[0036] In operation, plating apparatus 500 may receive a substrate on the lower surface 504 of the substrate support member 503. The receiving of the substrate by the substrate support member 503 may be conducted with the head assembly in an elevated position, i.e., with the substrate support member raised out of the top portion of chamber 502. In this position, a substrate transfer robot, such as transfer robot 102 shown in Figure 1, may be used to transport a substrate proximate substrate support member 503 when it is in an elevated position. Once a substrate is brought proximate to substrate support member 503, a vacuum source (not shown) may be brought into communication with the lower surface 504, and therefore, the substrate may be vacuum chucked to lower surface 504. Once the substrate is secured to substrate support member 503, head assembly 501 may lower substrate support member 503 into a processing position. The processing

position, for example, may be a position where the lower surface 504 is between about 1 mm and about 10 mm from bowl portion 507. Once the substrate is in a processing position, plating fluid may be dispensed through port 506. The plating fluid operates to fill the region 505 between the substrate and the bowl portion 507. Once the solution fills region 505, substrate support member 503 may be rotated and/or agitated to facilitate the plating process. Further, in similar fashion to the plating chamber shown in Figure 4A, the plating solution may be maintained in region 505 via a meniscus, or alternatively, an outer seal configuration may also be used. Further still, the plating solution may be continually dispensed from port 506 and allowed to flow outwardly across bowl portion 507 during the plating process.

[0037] Once a substrate is processed in plating chamber 107, regardless of the specific plating configuration used, the substrate may be removed therefrom by substrate transfer robot 102 and transferred to the spin rinse dry chamber 108. The transfer of the substrate from plating chamber 107 to spin rinse dry chamber 108 may include handing off the substrate by a first transfer robot 102 to a second transfer robot 102 via orienter/handoff location 103. Spin rinse dry chamber 108 generally includes a rotatably mounted substrate support member having a fluid dispense device positioned above the substrate support member. Thus, the substrate may be secured to the substrate support member, spun at a high rated speed, and have a rinsing fluid dispensed on the substrate surface. The centrifugal force of the spinning motion operates to urge the rinsing solution dispensed thereon, along with any surface contamination absorbed by the rinsing solution, outward toward the perimeter of the substrate and over the edge into a fluid drain. The flow of the rinsing solution onto the substrate surface may be terminated, and the substrate may continue to be spun by the substrate support member at a high rated speed, thus causing the remainder of the rinsing solution to be urged off of the substrate in a drying effect.

[0038] Once the substrate has been rinsed and dried in chamber 108, the substrate may be removed from chamber 108 by substrate transfer robot 102 and transferred to annealing chamber 109. Annealing chamber 109 may include a

substrate support member configured to receive and support a substrate thereon for an annealing process. Chamber 109 may further include a heating device, such as a resistive heating element or heating lamps, for example, that may be used for elevating the temperature in chamber 109 to a predetermined level for a predetermined time. The elevation of the temperature in chamber 109 operates to anneal the substrate positioned on the substrate support member in chamber 109. Once the annealing process of the substrate is complete in chamber 109, if the substrate transfer robot 102 may remove the annealed substrate from chamber 109 and transport the substrate to a substrate pod loader 105.

[0039] In operation, the exemplary plating system 100 of the invention may be used, for example, to plate copper onto substrates having sub-quarter micron sized features formed thereon. The substrates having sub-quarter micron sized features formed thereon may be stored in a cassette, which may be brought into communication with system 100 via selective attachment to substrate transfer chamber 101 via pod loader 104. Once pod loader 104 has received the cassette, robot 102 may operate to retrieve individual substrates from pod loader 104 for processing in system 100. Robot 102, for example, may retrieve a substrate from pod loader 104 and transfer the substrate into to activation chamber 106. Generally, the removal of a substrate from pod loader 104 includes opening a slit valve 110 positioned between chamber 101 and substrate pod loader 104. Similarly, when the substrate removed from pod loader 104 is to be introduced in to activation chamber 106, a slit valve 110, or other type of valve, between activation chamber 106 and substrate transfer chamber 101 may be opened such that the substrate may be introduced into chamber 106. Once the substrate is positioned in activation chamber 106, slit valve 110 may be closed in order to isolate activation chamber 106 from transfer chamber 101.

[0040] Once the substrate is positioned on substrate support member 212, the substrate may be vacuum checked to substrate receiving surface 214 the via application of a vacuum to aperture 224. Once the substrate is checked to substrate support member 212, substrate support member 212 may be rotated by motor 222.

While the substrate is rotated, fluid dispense nozzle 223 may dispense a rinsing solution onto the substrate surface. Thereafter, an activation solution may be dispensed on the substrate surface. Both the rinsing solution and the activation solution may be stored in a combination of fluid storage units 228, and selectively mixed/applied to the substrate surface via selective actuation of valves 229. The rotation of substrate support member 212 allows for the solution dispensed thereon to be evenly distributed across the surface of the substrate, as the solution is urged radially outward by the rotation of substrate support member 212. The outwardly urged solution either runs off of the edge of substrate support member 212, or is received in an annular fluid drain positioned around the perimeter of substrate support member 212. The solution is then communicated to bottom portion 207 of chamber 106, and is received in fluid drain 227 for capture and possible recycling. Once the activation solution is dispensed on the substrate surface, a rinsing solution may again be applied to the substrate surface.

[0041] Once the activation process is complete, the substrate may be removed from activation chamber 106 by substrate transfer robot 102 via opening of slit valve 110 between transfer chamber 101 and activation chamber 106. Robot 102 may then transfer the substrate to plating chamber 107 through another slit valve 110 positioned between plating chamber 107 and transfer chamber 101. Assuming the embodiment of plating chamber 107 shown in Figure 3A is utilized, the substrate may be positioned on substrate support member 301 by robot 102. A vacuum may then be applied to the backside of the substrate in order to vacuum chuck the substrate to the substrate support member 301. Substrate support member 301 may then be rotated via a activation of motor 311, while a plating solution is dispensed on the substrate surface by fluid dispense nozzle 315. The rate of rotation of the substrate support member during the solution dispensing process may be, for example, in the range of about 50 RPM to about 2000 RPM. The rotation of substrate support member 301 causes the plating solution to travel radially outward across the surface of the substrate, and therefore, the plating solution runs off of the edge of substrate support member 301 and is captured in a fluid drain of chamber 300. The fluid drain may be in communication with an

electrolyte replenishment system configured to replenish the electrolyte solution for subsequent uses. Once the plating process is complete, the substrate may be removed from the plating chamber. Removal of the substrate from plating chamber 300 again involves moving substrate transfer robot 102 into chamber 300 for the purpose of retrieving the plated substrate. The retrieving process may include actuation of lift pins 309, such that robot 102 may be able to engage the underside of the plated substrate for removal from chamber 300. Once robot 102 has retrieved the substrate from the plating chamber, the substrate may be transferred to a spin rinse dry chamber 108. The process of transferring the substrate to spin rinse dry chamber 108 may include handing off the substrate from a first substrate transfer robot to a second substrate transfer robot via a handoff station/orienter 103.

[0042] Alternatively, if the plating chamber illustrated in figure 4A is utilized, a slightly different plating method may be employed. For example, using chamber 400, operation shield 403 may first be moved to a substrate loading position, such that a substrate may be positioned on substrate support member 401 in chamber 400. Once the substrate is positioned on substrate support member 401, the evaporation shield 403 may be moved into a processing position. The processing positioned may, for example, include positioning the lower surface 404 of the evaporation shield 403 approximately 3 to 5 mm above the substrate surface. Alternatively, the spacing may be in the range of about 1mm to about 10mm. With the evaporation shield in a processing position, the plating solution may be dispensed by fluid dispense arm 402 into the interior portion of evaporation shield 403. The evaporation shield 403 communicates the plating solution to the region 408 between the substrate and the evaporation shield 403. A calculated amount of plating solution may be dispensed by fluid dispense arm 402, such that region 408 is filled, and a meniscus 407 forms approximate the perimeter of the substrate to be plated. Once region 408 is filled and meniscus 407 is formed, substrate support member 401 and evaporation shield 403 may be rotated relative to each other. The rotation of the respective members may include rotating only the substrate support member 401, only the evaporation shield 403, or both the substrate support member 401 in the evaporation shield 403. Further, the rotation may include a reversing the

direction of the respective members to essentially agitate back and forth. Regardless, the rotation of the respective members causes the plating solution in region 408 to be circulated, and therefore, facilitates plating. However, during the circulation process, introduction of additional plating solution is generally not required, as meniscus 407 maintains the plating solution in region 408. Therefore, the plating chamber illustrated in figure 400 utilizes substantially less plating solution than conventional devices configured to continually dispense a plating fluid onto the substrate surface.

[0043] When the plating process is completed in chamber 400, the rotation of substrate support member 401 may be increased, such that the centrifugal force generated by the rotation overcomes the meniscal force. This causes the plating solution in region 408 to be urged outward and subsequently captured by the fluid drain. The evaporation shield 403 may then be moved into a loading position, and the substrate may be removed from chamber 400 by robot 102 for transport to the next chamber in the plating process, which may be the spin rinse dry chamber 108.

[0044] Once the substrate is positioned in the spin rinse dry chamber 108, the substrate is generally chucked to a rotatably mounted substrate support member. The substrate support member is then rotated while a rinsing solution is dispensed on the substrate surface. The rotation rate of the substrate support member may be in the range of about 30 rpm to about 10,000 rpm, however, it is contemplated that the rotation of rotation may be lowered to as low as about 10 rpm and raised as high as about 30,000 rpm. Regardless of the rotation rate, the rinsing solution is urged outwardly across the surface of the substrate, and therefore, the rinsing solution operates to wash away any residue plating solution or unattached particles that reside on the substrate surface. The dispensing of the rinsing solution may then be terminated, while the rotation of the substrate support member is continued. The continued rotation of the substrate support member operates to urge the remainder of the rinsing solution off of the substrate surface, thus drying the substrate surface. The rate of rotation of the substrate support member during the rinsing and drying

process may be increased from the rotation rate of the rinsing process, *i.e.*, in the range of about 2,000 rpm to about 10,000 rpm or more, for example.

[0045] Once the rinse and dry process is complete, the substrate may be transferred to anneal chamber 109. In anneal chamber 109, the substrate may be positioned on a substrate support member, while the temperature within chamber 109 is elevated to a predetermined temperature for a predetermined period of time. The predetermined temperature and duration may be determined in accordance with a semiconductor processing recipe, where the temperature and duration are calculated to sufficiently anneal the layer plated on the substrate in plating chamber 107.

[0046] Once the annealing process is complete, the substrate may be removed from annealing chamber by transfer robot 102 and positioned in a substrate receiving pod loader 105. Generally, substrate receiving pod loader 105, along with substrate pod loader 104, are pod loaders configured to receive cassettes that may be selectively detached from transfer chamber 101. Therefore, substrates to be plated may be introduced into system 100 by a cassette placed in pod loader 104, while finished or plated substrates may be removed from system 100 by pod loader 105.

[0047] In another embodiment of the invention, plating chamber 107 and spin rinse dry chamber 108 may be combined into a unitary chamber. In this embodiment, the unitary chamber may be configured to rotate and dispense the plating solution on the substrate during a first stage, and then to rotate the substrate at a higher rate of speed while dispensing a rinsing solution and spin drying the substrate in a second stage. However, when the plating and rinse/dry chamber is are combined, it becomes increasingly difficult to recapture the plating solution, as the rinsing solution may become mixed therewith. Therefore, if the combined chamber embodiment is implemented, generally, the plating solution will not be reused. However, it is contemplated that a separation device may be implemented in the drain portion of the chamber in order to separate the plating solution from the rinsing solution, thus allowing for recapture of the plating solution.

PATENT

Attorney Docket No.: AMAT/6120/CPI/ECP/PJS

Express Mail No.: EL913564858US

[0048] While the foregoing is directed to embodiments of the present invention, other and further embodiments of the invention may be devised without departing from the basic scope thereof, and the scope thereof is determined by the claims that follow.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2